IT'S FINALLY HERE.

A MACHINE THAT CHARGES
MEMBER ACCOUNTS AUTOMATICALLY.





HOW IT WORKS

- We connect the machine to your gym's ABC Financial DataTrak account.
- 2 Members scan a barcode from a fob or smartphone to begin purchase.
- For security, members enter a phone number on file using the machine's keypad.
- Card on file is charged, sale is recorded in DataTrak, product dispenses.

BENEFITS

Increased member convenience

Front desk labor savings because members can self-serve, even without their wallet

24x7 access

Reduced product theft

AVAILABLE MODELS



Regular (Black)




Gray



Slim Black



Slim Gray



Sample Configuration

Adjustable Snack & Food Selections

Configurable to almost any package size in the field with no need for tools. Full selection (5-3/4"W) 3/4 selection (4-5/16"W) Single selection (2-7/8"W)



Standard Delivery Assist for Full ADA Compliance

Product is delivered at 15"
via manual lift and
actuated by
product door entry.



Energy Efficient

- Uses only 4.2 Kwh/day @ 75°F (24°C), 45% RH based on refrigerating 34.6 cu.ft. of space
- Low-E Argon filled insulated glass
- LED lighting
- Thickest foaming on the market with Eco-friendly BASF Autofroth® foaming process
- Balanced airflow design
- Energy saving programmable shutdown modes
- Eco-friendly refrigeration system

Versatile Steel Beverage Trays

Hold up to 60 canned or bottle beverages and come in 10 select or 9 select versions for wider product



Configure to meet your merchandising needs.

Movable barrier tray allows you to adjust temperature zones.







Intertek





| Alpine VT5000 | |
|----------------------------|--|
| Selections | Up to 60 items |
| Capacity | Varies with tray configuration |
| Selection Pricing | Individual from \$0 to \$655.35 |
| Payment Systems | All Industry standard MDB compatible devices |
| Data Communication | DEX/UCS |
| Electrical Requirements | Domestic: 115 VAC/60Hz, 9.5 AMPS International: 230 VAC/50Hz, 4.8 AMPS; With Heated Glass: 115 VAC/60Hz, 10.5 AMPS International: 230 VAC/50Hz, 5.2 AMPS |
| Refrigeration | Super 1/3 HP, R134a Closed System |
| Dimensions | Height 72"(183 cm) Width 41" (104 cm) Depth 38" (97 cm) |
| Net Weight | *838 lbs. (380.1 kg) *Varies with tray configuration and options. |
| Standard Features | GVC2 Controller, LED Lighting, iVend® Sensor System, Can & Bottle Trays, Heated Glass, Motor Pairing Capable |
| Options | Delivery Assist Box, iCart Touch screen Interface, inDEX Tool, 6th Tray, 9 Select Can/Bottle Tray Dual Coil, High Capacity Can Tray, inDEX Tool, Custom Coil and Tray Configurations, Custom Colors, Custom Graphics, Kick Panel |

In order to bring you the best products possible, we continue to improve product design and performance and as such specifications are subject to change without notice. The manufacturer makes no warrantees or representations of compliance with any local, state, national or international requirements for the operation of the equipment in any application for which it is capable of being used beyond the UL and NAMA approvals listed on the product. Any purchaser is required to make an independent analysis of the fitness and legality of the product's usage before it is deployed and must continue to monitor the potential changing nature of compliance requirements. The manufacturer expressly disclaims responsibility for compliance with any laws and affirmatively requires any buyer to make an independent analysis of the fitness and legal basis of any use or application of the subject unit.

